



## High Performance Short Throw Laser Projector

### FEATURES

- DLP® DarkChip3™ and BrilliantColor™ technologies for optimal black levels and vibrant colorful images
- 6100lm high brightness with 30,000 hrs (Eco) laser life
- 0.50:1 Short Throw Ratio
- IP6X high standard Anti-Dust compliant
- Delivers up to a 300" image from a distance close to the projection surface
- Rec 709 excellent color performance-coverage 95%
- Constant Brightness to keep the brightness constant
- 360° (degree) positioning for flexible installation
- H/V keystone / 4 corner geometric adjustment
- HDBaseT™ interface for the transmission of high-quality audio and video data over 100M
- Crestron® RoomView™ integration for network monitoring and management
- Power USB-A (5V/1.5A)
- Support 24/7 operation



The DU4381Z-ST projector is the ideal for a wide range of applications, including corporate, education, as well as galleries and museum.

Experience the difference with the ultimate short-throw projector DU4381Z-ST that provides effortless and discreet positioning options in close proximity to the projected surface. This versatile WUXGA laser projector offers an impressive picture with a brightness of 6100 lumens. Along with 0.5 short throw lens, 360-degree positioning option and optimal thermal management allow for a picture perfect installation both in single set up as well as in mapping applications.



## DU4381Z-ST

### SPECIFICATIONS

Image	<b>Display Type</b>	Single chip DLP® Technology by Texas Instruments
	<b>Brightness</b>	6100 ANSI Lumens
	<b>Native Resolution</b>	WUXGA (1920x1200)
	<b>Max. Supported Resolution</b>	WUXGA (1920x1200)
	<b>Contrast Ratio</b>	30,000 :1
	<b>Native Aspect Ratio</b>	16:10
	<b>Keystone Correction</b>	Vertical: +/-15°, Horizontal +/-15°
Optical	<b>Throw Ratio</b>	0.5:1
	<b>Image Size (Diagonal)</b>	60" - 325"
	<b>Projection Distance</b>	0.65 - 3.5 m
	<b>Projection Lens</b>	F/2.8 , f=7.46 mm
	<b>Zoom Ratio</b>	Fixed
	<b>Offset</b>	121%(Full) / 110.5%(Half)
	<b>Focus</b>	Manual
Features	<b>Features</b>	3D Features, 3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential), Keypad lock
Connectivity	<b>I/O Connection Ports</b>	VGA-In (15pin D-Sub) (1x), HDMI Number of Ports 1.4a (3x), Composite Video (1x), Audio-In (RCA) (1x), Audio-In (Mini-Jack) (1x), VGA-Out (15pin D-Sub) (1x), RJ45 (2x LAN / HDBaseT), IP Telnet Capable Over RJ-45, RS-232 (1x ), 3D-Sync (1x 3D Sync out), USB A (1x 5V 1.5A), USB miniB (Service), Microphone (Mini-Jack) (1x), Remote Jack(wire remote)
General	<b>Dimensions (W x D x H)</b>	360 x 440 x 186.3 mm
	<b>Weight</b>	10.5 kg
	<b>Noise Level</b>	36dB/34dB (Normal/Eco. Mode)
	<b>Power</b>	AC 100-240V, 50/60Hz
	<b>Control Software</b>	PJ - Control V3.0.0.4
	<b>Warranty</b>	Standard Laser Phosphor Projector Warranty: 5-Year warranty on projector/ 5-year or 10000h on the Laser Phosphor illumination source (whichever comes first)
	<b>Standard Accessories</b>	Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), R/C Wire 3.5mm Jack, AC Power Cord
	<b>Optional Accessories</b>	Remote Control P/N (5041846602)
	<b>UPC Code</b>	813097025708